

ACCESSORI

■ STANDARD □ OPTIONAL

DESCRIPTION	DUPLO 30 T	DUPLO 25/2	DUPLO 20/2 T	NOTE
Loading capacity 3000 kg on the platform with roof with tiles	■			
Loading capacity 2500 Kg on each platform		■		
Loading capacity 2000 kg on the platform and the roof			■	
Nr. 1 platform lift with 4 telescopic electro-hydraulic columns	■	■	■	
Nr. 1 platform with electrostatics galvanized smooth staves	■		■	
Nr. 2 platforms with electrostatics galvanized smooth staves		■		
Cover roof tileable predisposition	■		■	Tiles weight max 70 kg/m ²
Cover transittable roof	■		■	Transitability of the roof max 3000 kg
Complete hot dip galvanized structure	■	■	■	Silver RAL 7040 varnished columns excluded
Mechanical compensation with pins and chains	■	■	■	
Nr. 4 lifting cylinder with parachute valve	■	■	■	
Nr. 4 safety electro mechanical locks	■	■	■	
Nr. 1 "Dead man present" push button board with key IP 65	■	■	■	
Nr. 1 Electrical panel board on board the platform	■	■	■	
Nr. 1 hydraulic pump with motor on board the platform	■	■	■	
Nylon package	■	■	■	
Screws anchor	■	■	■	
Standard power supply 230-400 V/Ph/50 - 460 V/3Ph/60	■	■	■	
Platform width 2200, 2700 mm	□	□	□	
Monophase power supply 220V/Ph/50-60 Hz	□	□	□	
Non standard power supply	□	□	□	On request
Flashing light	□	□	□	
Audible warning kit	□	□	□	
Internal lightening led device in low voltage	□	□	□	
Nr. 2 Photocells barriers car control forward backward H=600 mm	□	□	□	
Photocell control car's presence on the roof	□		□	
Push button board in stainless steel	□	□	□	
Remote control each receiver	□	□	□	Max. ray 5 mt
Remote control each transmitter	□	□	□	Max. ray 5 mt
Hydraulic pump with low acoustic emission	□	□	□	On request
Hand pump kit	□	□	□	
Angular bar for protection in stainless steel	□	□	□	
Pallet kit for shipping	□	□	□	
Control unit on wooden crate	□	□	□	