DESCRIPTION	MOVE 30 L	MOVE 30 L - T	NOTE
standard Color BLUE RAL 5005 and SILVER RAL 7040	•	-	
Nr. 2 columns with cylinders and tooth rack			
Nr. 1 checker plate platform			
Nr. 1 torsion bar			
Nr. 2 "Dead man present" push button board with key at the floors - residential design - IP 54	•	-	
Security control module for sensors and safety locks			
N. 2 Electromagnetic sensors or N. 2 safety mechanical locks			
Nr. 1 hydraulic pump with motor			
Nr. 1 Electrical panel board			
standard power supply 230-400 V/3Ph/50 Hz- 460 V/3Ph/60 Hz	•	-	
Nr. 1 slowing kit			
Standard travel up to 4 mt.	-		
N. 2 stops			
N. 2 stopping wheels L = 745 mm			
Mechanical loking devices each level			
Nylon packaging	-		
Anchoring screws			
Emergency push button with key for pit access	-		
Transittable roof in checker plate		•	Roof transitability: max. 3000 kg. (Not suitable for lifting vehicle)
Stainless steel laying edge			
Tileable and transittable roof with tray 30 mm depth			Roof transitability: max. 3000 kg. (Not suitable for lifting vehicle) Tiles weight allowed max 70 Kg / m2; Pit has been modified for tile thickness
reverse guides			
Travel over 4 mt. up to 6.5 mt (each 500 mm.)			
Travel over 6.5 mt. up to 11 mt (each 500 mm.)			Applicable up to max. H=11 mt for MOVE 30 L and H=10 mt for MOVE 30 L + T $$
Travel over 11 mt. up to 16 mt (each 500 mm.)			Applicable up to max. H=16 mt (just for MOVE 30 L)
Platfor in 4 pieces			
Additional cost for non standard platform			
Non standard roof			
Additionl stop (3rd stop)			
Further additional stop			Applicable up to max 6 stops
Junction for columns splitted in two or more pieces			Verify accessibility to the shaft
Increasing speed (from 0,06 to 0,14 m/sec.)			Valid for a travel up to 6.5 mt (just move 30 L)
Increasing speed (from 0,10 to 0,15 m/sec.)			Valid for travel from 6.5 up to 11 mt for MOVE 30 L and for all travels up to 10 mt for MOVE 30 L + T
Increasing speed (from 0,08 to 0,15 m/sec.)			Valid for a travel form 11 mt up to 16 mt. (just for Move 30 L)
Additional push button board			
Push button board residential design			
Stainless steel push button board			
Additional magnetic sensor			
additional mechanical locking stopper			Control for manual doors
Predisposition for electromechanical safety lock Kronenberg or Prudhomme			Control for manual doors
Outside pulse call for each push button board			Applicble on a enclosed shaft
Automatic repositioning platform at home position (just with pulse call option)			Applicble on a enclosed shaft
Automatic repositioning platform in case of fire			Applicble on a enclosed shaft
Receiver for remote control use			Operational distance max. 5 m
Transmitter for remote control use			Operational distance max. 5 m

Flashing light		
Siren		
Trafic light (two colors)		
Trafic light (two colors) residential design		
Soft Starter		
Hydraulic pump with low acoustic emission		On request
manual pump for emergency descent maneuver		
Back up battery for auxiliaries circuits		Allows the emergency descent with platform not hanged to the floor
Waterproof galvanized cover for control unit for outdoor installation		
Set of Nr. 2 cylinders underneath the platform for stabilizing position		
Nr. 1 fix handrail H=1.200 mm. (per meter)		
Nr. 1 removable handrail H = 1.200 mm (per meter)		
Fix external ramps in 2 pieces		Verify installation procedure with OMER
one fix external ramp - 1 piece		Verify installation procedure with OMER
Nr. 2 photocells barriers H=600 mm., for car mouvement back and forward		Including supporting columns
Nr. 2 photocells barriers H=900 mm., for car mouvement back and forward		Including supporting columns
N. 2 photocells for car roof precence control		
Photocells barriers for doors area control H= 150 mm		
Photocells barriers for doors area control H= 300 mm		
Laser scanner		
Antivibration pads		On request
Non standard power supply		On request
Non standard color		
Interpon + powered coated painting (platform, columns and guides)		
Interpon + powered coated painting over 4 mt. (each 500 mm)		
Interpon + powered coated painting for non standard platform		
Interpon + powered coated painting for non standard roof		
Hot dip galvanization (Platfrom, columns and guides)		
Hot dip galvanization for standard roof		
Hot dip galvanization over 4 mt. (each 500 mm)		
Additional cost for hot dip galvanization non standard platform		
Hot dip galvanization for non standard roof		
Hot dip galvanization fix ramps in two pieces		On request
Hot dip galvanization long fix ramp		On request
tooth rack on pallet		
Piattaform on pallet		
Control panel crate		