ACCESSORI

DESCRIPTION	TOTALREX PF	NOTE
standard Color BLUE RAL 5005 and SILVER RAL 7040	•	
Nr. 1 Standard platform with electrostatics galvanized smooth staves		
Max. travel 3.500 mm.		
Nr. 2 bases for pit fixing		
Nr. 2 Lifting Cylinders		
Nr. 1 "Dead man present" push button board with key on top of the platform - residential design - IP 54		
N. 2 push button board - residential design "dead man present" with key, at floors IP 54	•	
Security control module for sensors and safety locks		
N. 2 Electromagnetic sensors or N. 2 safety mechanical locks		
Nr. 2 photocells barriers H=600 mm., for car mouvement back and forward		
Emergency auto dialer		Based on norm EN 81 - 28
N. 1 acoustic warning		
Nr. 1 hydraulic pump with motor		
Nr. 1 Electrical panel board		
standard power supply 230-400 V/3Ph/50 Hz- 460 V/3Ph/60 Hz		
N. 2 stopping wheels L = 745 mm		
2 stops		
Nylon package		
Anchors screws		
Emergency push button with key for pit access		
Non standard platofrm		
Hot dip galvanized staves for standard platform		
Hot dip galvanized staves for non standard platform		
bearing wheel for intensive use		advised for 10 cycles a day
Additional stop (third stop)		
additional push button board residential design		
Additional push button board with upright support for double entrance and exit - residential design		
stainless steel push button board		
Additional push button board with upright support for double entrance and exit - residential design in stainless steel		
additional electromagnetic sensor		
Additional mechanical safety lock		Control for manual doors
Predisposition for electromechanical safety lock Kronenberg or Prudhomme		Control for manual doors
Outside pulse call for each push button board		Applicble on a enclosed shaft
Automatic repositioning platform at home position (just with pulse call option)		Applicble on a enclosed shaft
Automatic repositioning platform in case of fire		Applicble on a enclosed shaft

Receiver for remote control use	Operational distance max. 5 m
Transmitter for remote control use	Operational distance max. 5 m
Flashing light	
Siren	
Trafic light (two colors)	
Trafic light (two colors) residential design	
Waterproof galvanized cover for control unit for outdoor installation	
Soft Starter	
Hydraulic pump with low acoustic emission	On request
manual pump for emergency descent maneuver	
Nr. 1 fix handrail H=1.200 mm. (per meter)	
Nr. 1 removable handrail H = 1.200 mm (per meter)	
Photocells barriers for doors area control H= 150 mm	
Photocells barriers for doors area control H= 300 mm	
Nr. 2 photocells barriers H=900 mm., for car mouvement back and forward	Including supporting columns
Nr. 2 photocells barriers H=1200 mm., for car mouvement back and forward	
Nr. 2 photocells barriers H=1500 mm., for car mouvement back and forward	
Nr. 2 photocells barriers H=1800 mm., for car mouvement back and forward	
Supporting structure for photocells barriers (H=1200, 1500, 1800 mm)	
GSM interface with 20 mt. length cable.	
Laser scanner	
Kit n. 4 platform ground supports	
non standard power supply	On request
non standard Color	
Interpon + powered coated painting totalrex PF	
Interpon + powered coated painting for non standard platform	
Hot dip galvanization (Platfrom, bases and scissor)	Platform, scissor and bases
Additional cost for hot dip galvanization non standard platform	
Platform on pallet	
Control panel crate	