

TOTALREX

	Tragkraft	Standardhub	Max. Hub	Min. Hebebühne	Standard-Hebebühne	Max. Hebebühne	Abstand der Hebebühne	Grube	Leistung	Geschwindigkeit	Versorgung	Standardgewicht	Hinweise
TOTAL REX PF	3.000 kg.	3.500 mm	3.500 mm	2320X4700 mm	2850x5200 mm	3000x5600 mm		510 mm	4 kw	0,06 m/s	400 v / 50 hz	3.100 kg.	
	6.608 lbs	137,8 inch	137,8 inch	91,3x185 inch	112,2x204,7 inch	118,1x220,5 inch		20,1 inch	5,4 hp	2,4 inch/s	400 v / 50 hz	6.828 lbs	
TOTAL REX 30 GOLD	3.000 kg.	4.100 mm	4.100 mm	2450X5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4.000 kg.	
	6.608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	8.811 lbs	
TOTAL REX 25 GOLD + T	2.500 kg.	4.100 mm	4.100 mm	2450X5200 mm	2850x5200 mm	3000x6000 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5.800 kg.	T= Dach Minimale Hubhöhe Von 2800mm für Plattform über 5600mm
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12.775 lbs	
TOTAL REX 20 GOLD + TP	2.500 kg.	4.100 mm	4.100 mm	2450X5200 mm	2850x5200 mm	3000x6000 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5.600 kg.	T= Dach Minimale Hubhöhe Von 2800mm für Plattform über 5600mm
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12.335 lbs	
TOTAL REX 30 GOLD F	3.000 kg.	4.100 mm	4.100 mm	2450X5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4.100 kg.	F= Geflanscht/ Gekuppelt
	6.608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	9.031 lbs	
TOTAL REX 25 GOLD F + T	2.500 kg.	4.100 mm	4.100 mm	2450X5200 mm	2850x5200 mm	3000x6000 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	6.000 kg.	F= Geflanscht/ Gekuppelt T=Dach
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch	82,7 inch	20,31 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	13.216 lbs	
TOTAL REX 20 GOLD + TPF	2.500 kg.	4.100 mm	4.100 mm	2450X5200 mm	2850x5200 mm	3000x5560 mm	2.100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5.800 kg.	F= Geflanscht/ Gekuppelt T=Dach P= Dach mit Fliesen
	5.507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12.775lbs	
TOTAL REX 60 PLATINUM	6.000 kg.	4.200 mm	4.200 mm	2650X5900 mm	3000x6000 mm	3000x7000 mm		800 mm	7,5 kw	0,07 m/s	400 v / 50 hz	6.000 kg.	
	13216 lbs	165,4 inch	165,4 inch	96,5x232,3 inch	118,1x236,2 inch	118,1x275,6 inch		31,5 inch	10,1 hp	2,8 inch/s	400 v / 50 hz	13.216 lbs	
TOTAL REX 40 PLATINUM +T	4.000 kg.	4.200 mm	4.200 mm	2650X5900 mm	3000x6000 mm	3000x7000 mm	2.100 mm	800 mm	7,5 kw	0,07 m/s	400 v / 50 hz	7.700 kg.	
	8.811 lbs	165,4 inch	165,4 inch	96,5x232,3 inch	118,1x236,2 inch	118,1x275,6 inch	82,7 inch	31,5 inch	10,1 hp	2,8 inch/s	400 v / 50 hz	16.960 lbs	
TOTAL REX 35 PLATINUM +TP	3.500 kg.	4.200 mm	4.200 mm	2650X5900 mm	3000x6000 mm	3000x7000 mm	2.100 mm	800 mm	7,5 kw	0,07 m/s	400 v / 50 hz	7.500 kg.	
	7.709 lbs	165,4 inch	165,4 inch	96,5x232,3 inch	118,1x236,2 inch	118,1x275,6 inch	82,7 inch	31,5 inch	10,1 hp	2,8 inch/s	400 v / 50 hz	16.520 lbs	