

ACCESSORI

■ STANDARD □ OPTIONAL

DESCRIPTION	HYPERLIFT	HYPERLIFT + T	NOTE
Standard colors: BLU RAL 5005 and SILVER RAL 7040	■	■	
Standard height up to 4 mt.	■	■	
Nr. 4 columns complete with lifting cylinders and tooth racks	■	■	
Nr. 1 platform with varnished smooth staves	■	■	
Nr. 1 balance system with 5 torsion bars	■	■	
Nr. 1 "Dead man present" push button board of elevator type with keys on the platform IP 54	■	■	Complete with support
Nr. 2 "Dead man present" push button board of elevator type with keys on the floors IP 54	■	■	
Security control module for sensors and/or electric lock	■	■	
Nr. 2 Electro magnetic sensors or Nr. 2 electric locks	■	■	
Emergency auto-dialer	■	■	Based on the norm EN 81 - 28
Back up battery for auxiliary circuits	■	■	It allows emergency descent with platform not on floor
Nr. 1 hydraulic pump with motor	■	■	
Nr. 1 electric panel board	■	■	
Standard power supply 230-400 V/3Ph/50 - 460 V/3Ph/60 Hz	■	■	
Nr. 1 slowing kit	■	■	
Nr. 1 acoustic warning	■	■	
Nr. 4 protections on a column's side	■	■	Height= 2000 mm
Nr.2 stopping wheel	■	■	
2 stops	■	■	
Nr. 2 photocells barriers H=600 mm. For forward and backward control	■	■	
Adjustable Floor mechanical locking devices	■	■	
Nylon package	■	■	
Screws anchors	■	■	
Roof in diamond checker plate		■	Roof transittable: 3500 kg. (Not suitable to lift a vehicle)
Emergency descent maneuver (with manual pump)	□	□	
Tileable roof		□	Tile max. weight: 80 kg/m2. Roof transittable: 3500 kg (not suitable to lift a vehicle)
Additional cost for travel over 4 mt. (each 500 mm.)	□	□	Applicable up to max. H= 10 mt
Additional cost for travel over 10 mt. (each 500 mm.)	□	□	Applicable from 10 up to max. H=13 mt.
Additional cost for travel over 13 mt. (each 500 mm.)	□	□	Applicable from 13 mt up to max. H=15 mt.
Additional cost for non standard platform from 18 to 25 m2	□	□	
Additional cost for non standard platform from 25 to 32 m2	□	□	
Additional cost for non standard roof from 18 to 25 m2	□	□	
Additional cost for non standard roof from 25 to 32 m2	□	□	
Additional stop (third stop)	□	□	
Additional cost for additional stop	□	□	Applicable up to max. 6 stops
Columns split in two or more pieces (each split)	□	□	Verify accessibility of the shaft
Additional cost for speed increase (from 0,05 to 0,10 m/sec.)	□	□	Advised for higher height to 4 mt. - power supplied 2 x 7,5 Kw
Additional cost for speed increase (from 0,05 to 0,15 m/sec.)	□	□	Advised for higher height to 4 mt. - power supplied 3 x 7,5 Kw
Additional push button board at the floor	□	□	
Additional push button board at the platform	□	□	
Push button board on the floor in stainless steel	□	□	
Push button board on the platform in stainless steel	□	□	
Additional electromagnetic sensor	□	□	
Additional electric lock	□	□	For manual doors control
Predisposition for Kronenberg or Prudhomme electric lock	□	□	For manual doors control
Outside pulse recall for each push button board	□	□	Applicable just on enclosed shaft

Pulse command return to home position button (just with pulse manouver)	<input type="checkbox"/>	<input type="checkbox"/>	Applicable just on enclosed shaft
Automatic repositioning to the floor in case of fire (just with pulse manouver)	<input type="checkbox"/>	<input type="checkbox"/>	Applicable just on enclosed shaft
Remote control each receiver	<input type="checkbox"/>	<input type="checkbox"/>	Max.ray 5 mt
Remote control each transmitter	<input type="checkbox"/>	<input type="checkbox"/>	Max.ray 5 mt
Flashing light	<input type="checkbox"/>	<input type="checkbox"/>	
Siren	<input type="checkbox"/>	<input type="checkbox"/>	
Laser scanner for area control	<input type="checkbox"/>	<input type="checkbox"/>	
2 colors trafic light (Red/ Green)	<input type="checkbox"/>	<input type="checkbox"/>	
2 colors trafic light (Red/ Green) design style	<input type="checkbox"/>	<input type="checkbox"/>	
Led lights low voltage on platform	<input type="checkbox"/>	<input type="checkbox"/>	
Soft starter	<input type="checkbox"/>	<input type="checkbox"/>	
Nr. 1 fix handrail H=1200 mm. (per meter)	<input type="checkbox"/>	<input type="checkbox"/>	
Nr. 1 removable handrail H=1200 mm. (per meter)	<input type="checkbox"/>	<input type="checkbox"/>	
Photocell barrier for door's area control H=150 mm	<input type="checkbox"/>	<input type="checkbox"/>	
Photocell barrier for door's area control H=300 mm	<input type="checkbox"/>	<input type="checkbox"/>	
Platform cover of almond alluminium	<input type="checkbox"/>	<input type="checkbox"/>	
Additional cost for non standard platform of almond alluminium from 18 to 25 m2	<input type="checkbox"/>	<input type="checkbox"/>	
Additional cost for non standard platform of almond alluminium from 25 to 32 m2	<input type="checkbox"/>	<input type="checkbox"/>	
Cabin on board installed in the vain (two sides, standard measures)	<input type="checkbox"/>	<input type="checkbox"/>	Adaptable for doors installation on platform board
Cabin on board installed in the vain (three sides, standard measures)	<input type="checkbox"/>	<input type="checkbox"/>	Adaptable for doors installation on platform board
Cabin on board for garden use (two sides, standard measures)	<input type="checkbox"/>	<input type="checkbox"/>	Adaptable for doors installation on platform board
Cabin on board for garden use (three sides, standard measures)	<input type="checkbox"/>	<input type="checkbox"/>	Adaptable for doors installation on platform board
Non standard power supply	<input type="checkbox"/>	<input type="checkbox"/>	On request
Hydraulic pump with low acoustic emission	<input type="checkbox"/>	<input type="checkbox"/>	On request
Non standard colour	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon bottom + varnishing (platforms, columns and guides)	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon bottom + varnishing (roof)		<input type="checkbox"/>	
Interpon bottom + varnishing over 4 mt. (every 500 mm)	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon bottom + platform varnishing from 18 to 25 m2	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon bottom + platform varnishing from 25 to 32 m2	<input type="checkbox"/>	<input type="checkbox"/>	
Interpon bottom + roof varnishing from 18 to 25 m2		<input type="checkbox"/>	
Interpon bottom + roof varnishing from 18 to 25 m2		<input type="checkbox"/>	
Hot dip galvanization (platform, columns and guides)	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization (roof)	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization over 4 mt. (every 500 mm.)	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization for platform from 18 to 25 m2	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization for platform from 18 to 32 m2	<input type="checkbox"/>	<input type="checkbox"/>	
Hot dip galvanization for roof from 18 to 25 m2		<input type="checkbox"/>	
Hot dip galvanization for roof from 18 to 32 m2		<input type="checkbox"/>	
Protection columns on pallet	<input type="checkbox"/>	<input type="checkbox"/>	
Control unit on wooden crate	<input type="checkbox"/>	<input type="checkbox"/>	