

REX GOLD

	Tragkraft	Standardhub	Max. Hub	Min. Hebebühne	Standard-Hebebühne	Max. Hebebühne	Nutzbare Höhe	Grube	Leistung	Geschwindigkeit	Versorgung	Standardgewicht	Hinweise
REX 30 GOLD	3000 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4000 kg.	
	6608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	8811 lbs	
REX 25 GOLD + T	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5800 kg.	T=Dach
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12775 lbs	
REX 25 GOLD + TP	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5600 kg.	T=Dach P=Dach mit Ziegeln
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12335 lbs	
REX 30 GOLD F	3000 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x6000 mm		510 mm	4 kw	0,05 m/s	400 v / 50 hz	4100 kg.	F=flanged
	6608 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x236,2 inch		20,1 inch	5,4 hp	2,0 inch/s	400 v / 50 hz	9031 lbs	
REX 25 GOLD F + T	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	6000 kg.	F= flanged T=Dach
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	13216 lbs	
REX 25 GOLD F + TP	2500 kg.	4100 mm	4100 mm	2450x5200 mm	2850x5200 mm	3000x5560 mm	2100 mm	510 mm	5,5 kw	0,05 m/s	400 v / 50 hz	5800 kg.	F= flanged T=Dach P=Dach mit Ziegeln
	5507 lbs	161,4 inch	161,4 inch	96,5x204,7 inch	112,2x204,7 inch	118,1x218,9 inch	82,7 inch	20,1 inch	7,4 hp	2,0 inch/s	400 v / 50 hz	12775 lbs	