

# TOTALMOVE

	Tragkraft	Standardhub	Max. Hub	Min. Hebebühne	Standard-Hebebühne	Max. Hebebühne	Abstand der Hebebühne	Grube	Leistung	Geschwindigkeit	Versorgung	Standardgewicht	Hinweise
TOTAL- MOVE 30 L	3.000 kg.	4.000 mm	16.000 mm	2.000x4.000 mm	2.865x5.200 mm	3.000x6.000 mm		250 mm	4/7,5 kw	0,06 m/s	400 v / 50 hz	3.700 kg.	
	6.608 lbs	157,5 inch	629,9 inch	78,7x157,5 inch	112,8x204,7 inch	118,1x236,2 inch		9,8 inch	5,5/10,2 hp	2,4 inch/s	400 v / 50 hz	8150 lbs	
TOTAL- MOVE 40 L	4.000 kg.	4.000 mm	13.500 mm	2.000x4.000 mm	2.865x5.200 mm	3.000x5.600 mm		390 mm	7,5 kw	0,09 m/s	400 v / 50 hz	4.200 kg.	
	8.811 lbs	157,5 inch	531,5 inch	78,7x157,5 inch	112,8x204,7 inch	118,1x236,2 inch		15,4 inch	10,2 hp	3,5 inch/s	400 v / 50 hz	9251 lbs	